

TOOLBOX TALKS

EQUIPMENT MOUNTING & DISMOUNTING

Toolbox Talks are designed to promote safety discussions and best practices on the jobsite. To see more Toolbox Talks, please visit hollandcs.com/toolboxtalks.

EQUIPMENT MOUNTING & DISMOUNTING

Safe access when mounting or dismounting various pieces of equipment is an essential part of workplace safety.

PROPER APPROACH:

- Always face equipment when mounting or dismounting
- Always use the access provided by the manufacturer

3 POINTS OF CONTACT:

- When mounting and dismounting equipment, personnel should always maintain contact with either 2 hands and 1 foot, or 1 hand and 2 feet. Failure to use this method can result in serious injuries
- Personnel should not carry anything in their hands while mounting or dismounting equipment. Tools and other objects should be handled after mounting and dismounting
- Maintain traction by ensuring footwear and footholds are free of potential hazards such as dirt, mud, ice, oil, grease or other debris

DISMOUNT

- Ensure ground is free from obstructions such as rocks, holes or other surface issues prior to dismount

INSPECTION AND MAINTENANCE

- Inspect access/egress areas for slip or trip hazards
- Ensure steps, grab bars and handrails are properly secured and free of defects and debris
- Ensure landing areas, if equipped, are free from obstructions and are equipped with adequate lighting

The material in this document is provided for informational purposes only and not as a comprehensive or exhaustive resource on this topic. This material has been compiled from a multitude of sources believed to be accurate; however, Holland assumes no responsibility for the accuracy or currency of this information and encourages you to consult experts in this area for more information. In no event does the content of this document supersede any applicable local, state or federal statutes or regulations.



A Better Way
• TO BUILD •